



# Auto Lamination

Touch screeb Auto feed Auto Cut Hot/Cold Laminating & Foiling



5 mins warming up

Easy Foil Function

- Stable buttom suction feeder
- Add Paper Without Pause
- Auto separation after lamination

	7" Touchscreen 6 sub menus Work Temprature / speed Mounting / setup / Help		Film perforation before separaton
	Stable buttom suction feeder		Easy and quick mounting After 4 steps
	Auto paper length measurement		Easy Foiling function
	5 mins warming up time		Anti curl function
	Auto separation with help of differential and booster		Manual lamination pressure

Model	350	360	370
Rollerwidth (mm)	370	370	370
Lamination width (mm)	182-350	182-350	182-350
Lamination length (mm)	182-470	182-470	182-470
Paper Weight (g)	150-300	150-300	150-300
Feeder volume	A4:20mm A3:10mm	A3:50mm	A3:50mm
Lamination speed (M/Min)	5	5	5
Max film diameter (mm)	200	200	200
Temp.range	0-150	0-150	0-150
110°C Warming up	5-8	5-8	5-8
Digital overlap	✓	✓	✓
Anti-curl level	18	18	18
Roll to roll	/	/	/
Rewinder	Optional	Optional	Optional
Cabinet	/	/	/
Power&Voltage	AC 220V 50/60HZ 1200W	AC 220V 50/60HZ 1200W	AC 220V 50/60HZ 1200W
N.W. (Kg)	120	120	120
Machine dimension (mm)	1452×680×540	1452×680×540	1452×680×540